





Power [kW] 1.6	Duty Cycle S1	Base speed [rpm] 18000	Base freq. [Hz] 300	Base voltage Δ [V] 220	Base voltage Y [V] 380	Protection IP54	Ins. Cl. F						
Min speed [rpm] 6000		Max speed [rpm] 18000	Max freq. [Hz] 300	Absorb. Δ [A] 8.1	Absorb. Y [A] 4.7	Part number on nameplate COM41470229							
Balancing: G2.5 - ISO 1940 @ maximum motor speed		Balancing type		tool type full key 	tool type half key 	Peso / weight 5.44 kg		Teknomotor S.r.l. Via Argenega 31, I-32038 Quero Vas (BL) www.teknomotor.com					
Tolleranze non quotate / unlisted tolerances: ±0.5mm Smussi non quotati / unlisted chamfers: ±0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \varnothing$		Title 4147-B-SB-P-ER20-RH				
rev. n° 00	description Emissione			date 15/02/2010	signature D. Bottarel	Customer Catalogo							
drawing - date D. Bottarel - 15/02/2010						approved - date S. Perli - 15/02/2010		checked - date S. Perli - 15/02/2010	sostituisce il sostituito dal	foglio / sheet 1 / 1	scala 1:2		A4